



## VTP-6

- H ..... Hot water
- h1 ..... Cold water
- h3,h4 ..... Supply and return pipe lower heat exchanger (TO1)
- h5,h6 ..... Supply and return pipe upper heat exchanger (TO2)
- h7 ..... Recirculation
- h8 ..... Drainage
- h9 ..... Pipe
- h10-h13 ..... Connecting the control-adjusting and measuring fixtures
- h14,h15 ..... Connecting magnesium anode
- h16 ..... Flange

V <sub>tank</sub> , l	Dimensions, mm				S <sub>TO1</sub> , m <sup>2</sup>	V <sub>TO1</sub> , l	S <sub>TO2</sub> , m <sup>2</sup>	V <sub>TO2</sub> , l	Mounting dimensions, mm														
	H	ØD1	ØD	Ød					h1	h3	h4	h5	h6	h7	h8	h9	h10	h11	h12	h13	h14	h15	h16
400	1730	700	600	450	1,95	14	1,00	7	331	991	331	1449	1141	1241	75	1116	331	916	1216	1481	1066	-	456
	1 1/4"								1"			3/4"	1 1/2"	1/2"		1"	-	456					
500	1980	700	600	450	1,95	14	1,25	9	331	991	331	1687	1291	1391	75	1116	331	916	1366	1731	1066	-	456
	1 1/4"				2,60*	19	1,00*	7*	1 1/4"	1"			3/4"	1 1/2"	1/2"		1"	1286*	-	456			
750	2035	850	750	600	1,90	14	1,05	8	357	885	357	1449	1185	1285	75	1010	357	810	1260	1757	960	-	482
	1 1/4"				2,95*	21*	1,40*	10*	1 1/4"	1"			3/4"	1 1/2"	1/2"		1"	1224*	-	482			
1000	2085	950	850	700	2,50	23	1,25	12	390	890	390	1440	1190	1290	75	1015	390	815	1265	1790	965	-	515
	1 1/2"				3,50*	32*	2,00*	19*	1 1/2"	1 1/4"			3/4"	1 1/2"	1/2"		1"	1165*	-	515			
1500	2170	1100	1000	850	2,80	26	1,55	15	430	880	430	1430	1180	1280	75	1005	430	805	1255	1830	955	1830	555
	1 1/2"				4,40*	40*	2,50*	23*	1 1/2"	1 1/4"			3/4"	1 1/2"	1/2"		1"	1205*	-	555			
2000	2260	1300	1200	1000	5,55	51	3,15	29	471	1171	471	1871	1471	1571	75	1296	471	1096	1546	1871	1246	1471	596
	2"				1 1/4"			1"	1 1/2"	1/2"		1"	-	596									

\*Dimensions refer to models with increased heat exchangers

Possible execution with working pressure of the tank 8, 10 bar