


400-10000 l  
Volume

3 bar  
95°C  
Max working pressure



# VTA-4

- H, h1-h3 ..... Fitting pipes for delivery and return lines of heating circuits
- h5 ..... Technologic fitting pipe
- h6-h8 ..... Fitting pipes for temperature sensors
- h9 ..... Flange Ø 120mm

V <sub>tank</sub> , l	Overall dimensions, mm				Fixing dimensions, mm								
	H	ØD1	ØD	Ød	h1	h2	h3	h4	h5	h6	h7	h8	h9
400	1700	800	600	450	264	834	-	1406	249	414	-	1256	336
	1½"				1½"			½"	¾"				
500	1995	800	600	450	264	721	1181	1634	249	414	964	1534	336
	1½"				1½"			½"	¾"				
750	2010	950	750	600	295	752	1212	1665	280	445	995	1565	367
	1½"				1½"			½"	¾"				
1000	2060	1050	850	700	323	780	1240	1693	308	473	1023	1593	395
	1½"				1½"			½"	¾"				
1500	2150	1200	1000	850	368	825	1285	1738	353	518	1068	1638	440
	1½"				1½"			½"	¾"				
2000	2250	1400	1200	1000	419	876	1336	1789	404	569	1119	1689	491
	1½"				1½"			½"	¾"				
3000	2340	1600	1400	1150	465	876	1336	1789	404	569	1119	1689	537
	2"				2"			½"	¾"				
4000	2400	1800	1600	1300	490	876	1336	1789	404	569	1119	1689	562
	2"				2"			½"	¾"				
5000	2900	1800	1600	1300	490	876	1336	1789	404	569	1119	1689	562
	2"				2"			½"	¾"				

Options working pressure of tank 6, 8 or 10 Bar are available  
 Dimensions for tanks volume 6000-10000 liters on request