


400-5000 l Volume
3 bar 95°C Max working pressure
6 bar 95°C Working pressure of heating circuit



VTA-3

H, h1-h4 Fitting pipes for delivery and return lines of heating circuits
 h5 Technologic fitting pipe
 h6-h8 Fitting pipes for temperature sensors
 h9 Flange Ø 120mm
 h12-h13 Fitting pipes for delivery and return lines of outer heating circuit (TO1-lower heat exchanger)

V _{tank} , l	Overall dimensions, mm				S _{TO1} , m ²	V _{TO1} , l	Fixing dimensions, mm										
	H	ØD1	ØD	Ød			h1	h2	h3	h4	h5	h6	h7	h8	h9	h12	h13
400	1700	800	600	450	1,5	10	264	834	-	1406	249	414	-	1256	336	248	688
	1½"						1½"			½"	¾"		1"				
500	1995	800	600	450	1,5	10	264	721	1181	1634	249	414	964	1534	336	248	688
	1½"						1½"			½"	¾"		1"				
750	2010	950	750	600	1,5	10	295	752	1212	1665	280	445	995	1565	367	279	631
	1½"						1½"			½"	¾"		1"				
1000	2060	1050	850	700	1,8	14	323	780	1240	1693	308	473	1023	1593	395	311	661
	1½"						1½"			½"	¾"		1¼"				
1500	2150	1200	1000	850	2,3	18	368	825	1285	1738	353	518	1068	1638	440	356	706
	1½"						1½"			½"	¾"		1¼"				
2000	2250	1400	1200	1000	2,3	18	419	876	1336	1789	404	569	1119	1689	491	407	707
	1½"						1½"			½"	¾"		1¼"				

Options working pressure of tank 6, 8 or 10 Bar are available
 Dimensions for tanks volume 3000-5000 liters on request