



200-3000 l
Volumes

6 bar
95°C
Working pressure tank

10 bar
95°C
Working pressure at the inlet to the heat exchanger

VTP-4

- H Hot water
- h1 Cold water
- h3,h4 Supply and return pipe lower heat exchanger (TO1)
- h7 Recirculation
- h8 Drainage
- h9 Pipe
- h10-h13 Connecting the control-adjusting and measuring fixtures
- h14,h15 Connecting magnesium anode
- h16 Flange

V _{tank} , l	Dimensions, mm				S _{TO1} , m ²	V _{TO1} , l	Mounting dimensions, mm												
	H	ØD1	ØD	Ød			h1	h3	h4	h7	h8	h9	h10	h11	h12	h13	h14	h15	h16
400	1730	700	600	450	1,95	14	331	991	331	1231	75	1191	331	891	1091	1481	1091	-	456
	1 1/4"						1"	3/4"	1 1/2"	1/2"		1"	-	Ø210					
500	1980	700	600	450	1,95	14	331	991	331	1231	75	1191	331	891	1091	1731	1091	-	456
	2,60*				19*	1211*	1331*	1411*	1111*	1311*	1311*	-	Ø210						
750	2035	850	750	600	2,05	15	357	929	357	1257	75	1129	357	829	1029	1757	1029	-	482
	2,95*				21*	1149*	1349*	1049*	1249*	1249*	-	Ø210							
1000	2085	950	850	700	2,75	26	390	940	390	1290	75	1140	390	840	1040	1790	1040	-	515
	3,50*				32*	1090*	1290*	990*	1190*	1190*	-	Ø210							
1500	2170	1100	1000	850	4,40	40	430	1130	430	1330	75	1330	430	1030	1230	1830	1230	1830	555
	1 1/2"				1 1/4"	3/4"	1 1/2"	1/2"		1"	-	Ø210							
2000	2260	1300	1200	1000	5,55	51	471	1171	471	1371	75	1371	471	1071	1271	1871	1271	1471	596
	2"				1 1/4"	1"	1 1/2"	1/2"		1"	-	Ø210							

*Dimensions refer to models with increased heat exchangers

Possible execution with working pressure of the tank 8, 10 bar