


400-2000 l
Volume

3 bar 95°C
Max working pressure

10 bar 95°C
Working pressure of DHW heat exchanger



VTA-2

- H, h1-h4 Fitting pipes for delivery and return lines of heating circuits
- h5 Technologic fitting pipe
- h6-h8 Fitting pipes for temperature sensors
- h9 Flange Ø 120mm
- h10-h11 Fitting pipes for cold and hot water pipelines (TO2-upper heat exchanger)

V _{tank} , l	Overall dimensions, mm				S _{TO2} , m ²	V _{TO2} , l	Fixing dimensions, mm										
	H	ØD1	ØD	Ød			h1	h2	h3	h4	h5	h6	h7	h8	h9	h10	h11
400	1700	800	600	450	1,4	10	264	834	-	1406	249	414	-	1256	336	930	1414
	1 1/2"						1 1/2"			1/2"	3/4"		1"				
500	1995	800	600	450	1,4	10	264	721	1181	1634	249	414	964	1534	336	?	1664
	1 1/2"				2,2	16	1 1/2"			1/2"	3/4"		1"				
750	2010	950	750	600	1,55	11	295	752	1212	1665	280	445	995	1565	367	903	1695
				2,3	14	903											
				3,1	22	903											
				3,8	27	903											
1 1/2"	1 1/2"			1/2"	3/4"		1"										
1000	2060	1050	850	700	1,55	14	323	780	1240	1693	308	473	1023	1593	395	819	1719
				2,3	22	819											
				3,1	29	819											
				3,9	36	819											
				4,6	42	819											
1 1/2"	1 1/2"			1/2"	3/4"		1 1/4"										
1500	2150	1200	1000	850	1,9	18	368	825	1285	1738	353	518	1068	1638	440	819	1764
				2,9	27	819											
				3,85	36	819											
				4,8	45	819											
				5,7	52	819											
1 1/2"	1 1/2"			1/2"	3/4"		1 1/4"										
2000	2250	1400	1200	1000	2,3	21	419	876	1336	1789	404	569	1119	1689	491	819	1815
				3,45	32	819											
				4,56	43	819											
				5,7	52	819											
				6,9	64	819											
1 1/2"	1 1/2"			1/2"	3/4"		1 1/4"										

Options working pressure of tank 6, 8 or 10 Bar are available